VAMPCO® Aluminum DOORS

VALLEY METAL PRODUCTS CO.

PLAINWELL
MICHIGAN

Subsidiary of
Mueller Brass Co.,
Port Huron, Mich.







2¾" x 5½" FRAME















2¾" x 7½" and
2¾" x 9½" deep
Frames are also
available

specifications

WORK REQUIRED: Aluminum narrow stile, wide stile or recessed panel, doors, frames, transoms, side lights and other items directly related shall be as manufactured by Valley Metal Products Company, Plainwell, Michigan.

MATERIALS: All sections shall be of extruded aluminum shapes of 6063-T5 alloy.
Section thickness shall be not less than .125" and glazing shapes shall not be less than .040".
All fastening parts such as screws, bolts, nuts, brackets and clips shall be fully protected against any chemical or electrolytic action.

WORKMANSHIP: All door corners shall be accurately joined and fitted to flush hairline joints. All corners shall be welded on unexposed sides. No weld marks such as halos, pitting or discoloration will be permitted on finish product.

All door welds shall thoroughly penetrate and produce a complete fusion of metals, and the corners shall be reinforced with a ⅜" aluminum rod with nuts on both ends giving an additional strength of not less than 20,000 P.S.I.

All fastening of glazing beads shall be of concealed type and no exposed screws shall be permitted.

Weatherstrip shall be of vinyl back pile cloth, securely held in place as provided in the extrusions of the doors and frames. The perimeter of the frames on single acting doors shall be weatherstripped as well as the meeting stile of double doors. Double acting doors shall be weatherstripped on the face of the stile on all outside stiles as well as the meeting stiles.

No surface application of weatherstripping will be permitted.

All cutouts, mortising, recesses or mill operation necessary for the installation of hardware shall be accurately made and where reinforcing is required, it shall be done with such material to insure adequate operation and strength.

The complete assembly shall be fabricated in the factory to insure accurately fitted joints, proper fitting hardware. No field fabrication of frames will be permitted.

FINISH: All exposed surfaces shall be finished free of die marks, scratches, weld halos or surface blemishes and given an anodic oxide treatment in accordance with Alcoa specification "Alumilite 204 A1 R1". Recessed Door panel finish shall be Vamchrome applied color, #10 Ribbed Aluminum, Plastic Fabricate Coated, Wood veneer or plain Aluminum 204 finish.

HARDWARE: All hardware shall be furnished and installed by the door manufacturer. No field application will be permitted. Hardware finish shall closely match the finish of the doors.

SHOP DRAWINGS: Drawings shall be furnished for approval in triplicate of a scale that will show all details clearly and with all dimensions necessary for coordination and installation.

PROTECTION: Surfaces of the aluminum placed in contact with any material such as steel, concrete or any other material that contains corrosive chemicals the aluminum shall be protected by an approved method by the erection contractor.

ERECTION: All items under this section shall be installed in prepared openings and be set plumb, square and level and all properly aligned to insure proper operation and must be under the guidance of factory trained personnel.

To insure proper operation the installation contractor and architect check and make any adjustments necessary for satisfactory operation.

All material under this contract shall carry a guarantee of one year against manufacture defect and any failure occurring under these circumstances the material will be replaced without charge to the owner.



Typical Elevations

1¾" x 4" FRAME
DETAILS SHOWN







SMALL LETTER S. IN DETAIL IDENTIFICATION DENOTES SINGLE ACTION. SMALL LETTER D. DENOTES DOUBLE ACTION DOORS.



NARROW STILE DOORS . . . . . ½ SIZE DETAILS













RECESSED PANEL DOORS





QUARTER SCALE





½ SIZE DETAILS



VAMPCO WIDE STILE DOOR



SPECIAL FRAMES FOR WIDE AND NARROW STILE DOORS

package units



3084D 3684D 4284D	3084DF 3684DF 4284DF	3084DFT 3684DFT 4284DFT	6084-2D 7284-2D 8484-2D	6084-2DF 7284-2DF 8484-2DF	6084-2DFT 7284-2DFT 8484-2DFT

D INDICATES DOOR ONLY F INDICATES FRAME T INDICATES TRANSOM
2 INDICATES PAIR OF DOORS



TUBULAR HORIZONTAL OR VERTICAL MUNTIN

VAMPCO PACKAGE DOOR consists of VAMPCO Narrow Stile Doors in standard sizes. Door closers of either overhead or floor type, VAMPCO pivot hinges, push and pull bars, dead lock and threshold and flush bolts for pairs of doors. VAMPCO STANDARD STOCK Side Lights are also available in 3 sizes.



4" x 4" SELF-MATING CORNER POST



4½" x 4½" HEAD JAMB FOR CONCEALED OVERHEAD CLOSERS

V-1
2'0" x 7'2"



V-2
2'0" x 10'4"

V-3
2'0" x 10'4"

VAMPCO

Aluminum doors

FLOOR TYPE
DOOR HOLDER



WALL TYPE
DOOR HOLDER

DROP ARM
DOOR HOLDER

OFFSET PIVOT
FLOOR CLOSER



CENTER PIVOT
FLOOR CLOSER



TUBULAR DEAD LOCK



DEAD BOLT LOCK



LOCKSET-WIDE
STILE DOORS



PANIC HARDWARE



FLUSH BOLT



THRESHOLD FOR FLOOR CHECK CLOSERS



LATCH LOCK



THUMB TURN



STANDARD PUSH-PULL BAR



STANDARD LOCK CYLINDER



INTERMEDIATE PIVOT HINGE

SPECIAL PULL BAR



BALL BEARING HINGE



SPECIAL PUSH BAR



SOFFIT BRACKETS FOR OUTSWINGING
DOORS

VAMPCO

Aluminum doors



DOOR CLOSER

SPECIAL NAME PLATE PUSH BAR



CONCEALED OVERHEAD CLOSER



VAMPCO OFFSET PIVOT HINGE



WEATHERSTRIPPING
BOTTOM RAIL



LETTER SLOTS



PUSH BAR



SPECIAL PUSH-PULL BAR



SPECIAL PUSH OR
PULL BAR SET

PRODUCERS' COUNCIL
AFFILIATED WITH THE AMERICAN INSTITUTE OF ARCHITECTS
ALUMINUM WINDOW MANUFACTURERS ASSOCIATION
AWM

Digitized by:

ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org

BUILDING
TECHNOLOGY
HERITAGE
LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

From the collection of:

Carol J. Dyson, AIA